

## Boiler Pipe Work Casing

Encasement 'Standard' casings can be used above or below the boiler, providing a simple, quick and cost effective solution for concealing gas and central heating pipe work as well as flues.

Manufactured from lightweight and durable 5mm thick FSC plywood, the single piece 'U' shaped casing is available in depth of 75, 100, 125, 150, 175 & 200 and Widths of 200, 400, 420 & 440 with optional heights of 295, 495 or 3000mm, which can easily be cut on site.

The casings are self-supporting, so can be free standing or secured using mechanical fixings or mastic adhesives, enabling easy removal for routine servicing or maintenance.

### **170 PREFORMED PLYWOOD CASINGS:**

#### **Manufacturer:**

Encasement Ltd, Peartree Business Centre, Enterprise Way, Bretton, Peterborough, Cambridgeshire PE3 8YQ. Tel: 01733 266 889. Fax: 01733 268 999.  
Email [technical@encasement.co.uk](mailto:technical@encasement.co.uk)

**Material:** FSC Full Chain of Custody Certified Products.

#### **Size:**

Length: 295mm, 495mm or 3000mm.  
Material thickness: 5mm.

#### **5mm**

Depth Range: 75, 100, 125, 150, 175, 200  
Width Range: 200, 400, 420, 440

#### **Finish/Colour:**

Finishes: White Melamine as standard, although other finishes are available in Laminates or real wood veneer.

Custom options are also available. Please contact our sales office with your width, depth, and height of the required casing.

NB - Contact Encasement Sales office for samples and colour swatches.

#### **Fixings:**

The casings are self-supporting, so can be free standing or secured using mechanical fixings or mastic adhesives, enabling easy removal for routine servicing or maintenance.

2x 25/38 FSC Timber Battens required fixed securely on the wall.

NB –A site survey service is available once the pipe work has been installed to ensure the correct profile is used. Drawings are available in a PDF & DWG format on

<http://encasement.co.uk/technical-drawings.aspx>